

Version number 1

Reviewed on 04/03/2023

1 Identification

· Product identifier

Trade name: XPLEX Bond Monomer, XPLEX Bond Modelling Liquid

- · Application of the substance / the mixture Bonding system for fixing denture teeth
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier: CANDULOR AG
 Boulevard Lilienthal 8
 8152 Glattpark (Opfikon)
 SWITZERLAND

Tel. +41 (0) 44 805 9000 *Fax* +41 (0) 44 805 9090

- Information department: Regulatory Affairs info@candulor.ch
- Emergency telephone number: 24 Hour Emergency Assistance: Emergency-Call USA - Infotrac: 1-800-535-5053 Emergency-Call Canada - Canutec: 1-613-996-6666

General SDS Assistance: US: 1-800-533-6825 Canada: 1-800-263-8182

2 Hazard(s) identification

· Classification of the substance or mixture

Flammable Liquids 2H225 Highly flammable liquid and vapor.Skin Irritation 2H315 Causes skin irritation.Sensitization - Skin 1H317 May cause an allergic skin reaction.Specific Target Organ Toxicity - Single Exposure 3H335 May cause respiratory irritation.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



- · Signal word Danger
- *Hazard-determining components of labeling:* methyl methacrylate 1,4-butanediol dimethacrylate
- Hazard statements Highly flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation.

(Contd. on page 2)


US

Printing date 04/03/2023

Version number 1

Reviewed on 04/03/2023

Trade name: XPLEX Bond Monomer, XPLEX Bond Modelling Liquid



[·] Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 04/03/2023

Version number 1

Reviewed on 04/03/2023

Trade name: XPLEX Bond Monomer, XPLEX Bond Modelling Liquid

(Contd. of page 2)

• *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information Cool endangered receptacles with water spray.

6 Accidental release measures

• *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

· Precautions for safe handling

Only adequately trained personnel should handle this product. Ensure good ventilation/exhaustion at the workplace. For use in dentistry only.

- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and receptacles:* Store in a cool location.
 Store only in the original receptacle. *Information about storage in one common storage facility:* Store away from oxidizing agents.
- Further information about storage conditions:
 Further information about storage conditions:
 Keep receptacle tightly sealed.
 Store receptacle in a well ventilated area.
 Protect from heat and direct sunlight.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

US

Printing date 04/03/2023

Version number 1

Reviewed on 04/03/2023

Trade name: XPLEX Bond Monomer, XPLEX Bond Modelling Liquid

(Contd. of page 3)

· Control parameters · Components with limit values that require monitoring at the workplace: The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit. At this time, the remaining constituent has no known exposure limits. CAS: 80-62-6 methyl methacrylate PEL Long-term value: 410 mg/m³, 100 ppm REL Long-term value: 410 mg/m³, 100 ppm TLV Short-term value: 410 mg/m³, 100 ppm Long-term value: 205 mg/m³, 50 ppm DSEN · Additional information: The lists that were valid during the creation were used as basis. · Exposure controls · Personal protective equipment: • General protective and hygienic measures: Usual hygienic measures for dental practice and dental laboratories. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Do not inhale gases / fumes / aerosols. • Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. · Recommended filter device for short term use: Filter A1 Filter A2 Filter A3 · Protection of hands: Protective gloves After use of gloves apply skin-cleaning agents and skin cosmetics. · Material of gloves Butyl rubber, BR Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. · Not suitable are gloves made of the following materials: Commercial medical gloves do not provide protection against the sensitizing effect of methacrylates. • Eye protection: Tightly sealed goggles US

(Contd. on page 5)

Version number 1

Reviewed on 04/03/2023

Trade name: XPLEX Bond Monomer, XPLEX Bond Modelling Liquid

(Contd. of page 4)

Information on basic physical and c	hemical properties
General Information	
Appearance:	
Form: Color:	Fluid Colorless
Odor:	
Odor: Odor threshold:	Pungent Not determined.
pH-value:	Not determined.
•	Not determined.
Change in condition	
Melting point/Melting range:	-48 °C (-54.4 °F)
Boiling point/Boiling range:	101 °C (213.8 °F)
Flash point:	10 °C (50 °F)
Ignition temperature:	430 °C (806 °F)
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
Vapor pressure at 20 °C (68 °F):	47 hPa (35.3 mm Hg)
Density at 20 °C (68 °F):	0.943 g/cm ³ (7.869 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water at 20 °C (68 °F):	1.6 g/l
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Other information	No further relevant information available.

10 Stability and reactivity

· *Reactivity* No further relevant information available.

- · *Chemical stability Stable under normal handling and storage conditions.*
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions
- Forms explosive gas mixture with air. Reacts with strong oxidizing agents.

Exothermic polymerization.

- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6)

US

Printing date 04/03/2023

Version number 1

Reviewed on 04/03/2023

Trade name: XPLEX Bond Monomer, XPLEX Bond Modelling Liquid

(Contd. of page 5)

3

· Hazardous decomposition products: None under normal conditions of storage and use.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

CAS: 80-62-6 methyl methacrylate

Oral LD50 7872 mg/kg (rat)

- Specific symptoms in biological assay:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information: No further relevant information available.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 80-62-6 methyl methacrylate

· NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- *PBT*: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Take to an approved landfill or a waste incineration plant, under conditions approved by the local authority.

(Contd. on page 7)

Printing date 04/03/2023

Version number 1

Reviewed on 04/03/2023

Trade name: XPLEX Bond Monomer, XPLEX Bond Modelling Liquid

(Contd. of page 6)

Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, ADR/RID/ADN, IMDG, IATA	UN1247
UN proper shipping name DOT ADR/RID/ADN IMDG, IATA	Methyl methacrylate monomer, stabilized solution 1247 Methyl methacrylate monomer, stabilized solution METHYL METHACRYLATE MONOMER, STABILIZED solution
Transport hazard class(es)	
DOT	
Class	3 Flammable liquids
Label	3
ADR/RID/ADN	
Class	
Label	3 (F1) Flammable liquids 3
IMDG, IATA	3 Flammable liquids 3
Packing group DOT, ADR/RID/ADN, IMDG, IATA	II
Environmental hazards: Marine pollutant:	No
Special precautions for user Hazard identification number (Kemler co EMS Number: Stowage Category Stowage Code	Warning: Flammable liquids ode): 339 F-E,S-D B SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	of Not applicable.

Safety Data Sheet acc. to OSHA HCS

Version number 1

Reviewed on 04/03/2023

Trade name: XPLEX Bond Monomer, XPLEX Bond Modelling Liquid

Transport/Additional information:	(Contd. of page)
ADR/RID/ADN Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED SOLUTION, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):	
CAS: 80-62-6 methyl methacrylate	
• TSCA (Toxic Substances Control Act):	
CAS: 80-62-6 methyl methacrylate	
CAS: 2082-81-7 1,4-butanediol dimethacrylate	
· Proposition 65	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
CAS: 80-62-6 methyl methacrylate	<i>E</i> , <i>N</i> .
· TLV (Threshold Limit Value)	
CAS: 80-62-6 methyl methacrylate	A
· NIOSH-Ca (National Institute for Occupational Safety and Health)	•
None of the ingredients is listed.	
• <i>GHS label elements</i> The product is classified and labeled according to the Globally Harmonized System (GHS).	
	(Contd. on page

Version number 1

Reviewed on 04/03/2023

Trade name: XPLEX Bond Monomer, XPLEX Bond Modelling Liquid

(Contd. of page 8) · Hazard pictograms GHS07 GHS02 · Signal word Danger · Hazard-determining components of labeling: methyl methacrylate 1,4-butanediol dimethacrylate · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray Do not get in eyes, on skin, or on clothing. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Dispose of contents/container in accordance with local/regional/national/international regulations. · National regulations: • Other regulations, limitations and prohibitive regulations The product is a medical device according to the Directive 93/42/EEC. This product is classified as a medical device under US and Canadian regulations and has been reviewed by the US Food and Drug Administration and Health Canada. Chemical safety assessment: A Chemical Safety Assessment has not been carried out. 16 Other information This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. · Contact: · Date of preparation / last revision 04/03/2023

• Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Skin Irritation 2: Skin corrosion/irritation - Category 2 (Contd. on page 10)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 04/03/2023

Version number 1

Reviewed on 04/03/2023

Trade name: XPLEX Bond Monomer, XPLEX Bond Modelling Liquid

(Contd. of page 9)

Sensitization - Skin 1: Skin sensitisation – Category 1 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3